

# Sulfonate-Grafted Porous Polymer Networks for Preferential CO<sub>2</sub> Adsorption at Low Pressure

Weigang Lu,<sup>†</sup> Daqiang Yuan,<sup>†</sup> Julian Sculley,<sup>†</sup> Dan Zhao,<sup>‡</sup> Rajamani Krishna,<sup>§</sup> and Hong-Cai Zhou<sup>\*,†</sup>

<sup>†</sup>Department of Chemistry, Texas A&M University, College Station, Texas 77842, United States

<sup>‡</sup>Chemical Sciences and Engineering Division, Argonne National Laboratory, Argonne, Illinois 60439, United States

<sup>§</sup>Van't Hoff Institute for Molecular Sciences, University of Amsterdam, Science Park 904, 1098 XH Amsterdam, The Netherlands

#### Supporting Information

**ABSTRACT:** A porous polymer network (PPN) grafted with sulfonic acid (PPN-6-SO<sub>3</sub>H) and its lithium salt (PPN-6-SO<sub>3</sub>Li) exhibit significant increases in isosteric heats of CO<sub>2</sub> adsorption and CO<sub>2</sub>-uptake capacities. IAST calculations using single-component-isotherm data and a 15/85 CO<sub>2</sub>/N<sub>2</sub> ratio at 295 K and 1 bar revealed that the sulfonategrafted PPN-6 networks show exceptionally high adsorption selectivity for CO<sub>2</sub> over N<sub>2</sub> (155 and 414 for PPN-6-SO<sub>3</sub>H and PPN-6-SO<sub>3</sub>Li, respectively). Since these PPNs also possess ultrahigh physicochemical stability, practical applications in postcombustion capture of CO<sub>2</sub> lie well within the realm of possibility.

One of the primary scientific discussions currently ongoing is that of global climate change, which is at least in part attributed to the increasing  $CO_2$  concentration in the air. Carbon capture and sequestration (CCS), a process to separate  $CO_2$ from flue gas, has been proposed as a feasible way to mediate the atmospheric  $CO_2$  concentration. Conventional  $CO_2$  capture processes employed in power plants worldwide are postcombustion "wet scrubbing" methods involving chemical adsorption of  $CO_2$  by amine solutions such as monoethanolamine (MEA). There are several disadvantages with wet scrubbing, including the considerable parasitic power consumption involved in the regeneration of the solutions and the measures that must be taken to control the corrosive solutions, both of which lead to reduced efficiencies and increased costs for electricity generation.<sup>1</sup>

An alternative, energy-conserving approach involves the use of porous materials, which can easily take up and release  $CO_2$  through a physisorption mechanism. Recently, metal–organic frameworks (MOFs), adsorbents made of metal ions and organic linkers with high surface areas and tunable pore sizes, have emerged to show remarkable  $CO_2$ -uptake capacities and  $CO_2/N_2$  selectivities at room temperature.<sup>2</sup> However, the majority of MOFs have difficulty in meeting the stringent industrial requirements.<sup>3</sup> On the other hand, purely organic porous polymers, another class of adsorbents with comparable surface areas and pore sizes, exhibit much higher physicochemical stability as a result of the covalent bonding nature of the network construction.<sup>4</sup> Despite the fact that most of them are amorphous, their stability is desirable in practical applications.

Besides physicochemical stability, high  $CO_2$ -uptake capacity and  $CO_2/N_2$  selectivity under ambient conditions are equally essential for porous materials to be industrially applicable. Presumably, increasing the isosteric heat of CO<sub>2</sub> adsorption through the introduction of CO<sub>2</sub>-philic moieties should have a great influence on both. Indeed, significant increases of isosteric heats and CO<sub>2</sub>/N<sub>2</sub> adsorption selectivity have been observed upon pre- or postsynthetic introduction of polar functionalities;<sup>5</sup> however, this approach usually has a negative impact on the surface area that can lead to very low CO<sub>2</sub>-uptake capacity if the surface area is severely compromised. One possible strategy to tackle this issue is to judiciously select porous polymers with ultrahigh surface areas and physicochemical stability as starting materials. Therefore, sufficient surface area can be retained after the introduction of CO<sub>2</sub>-philic moieties.


Herein we report the synthesis of PPN-6, a porous polymer network (PPN) with permanent porosity, and grafting of PPN-6 with sulfonic acid and lithium sulfonate. The resulting PPN-6-SO<sub>3</sub>H and PPN-6-SO<sub>3</sub>Li materials showed significant increases in CO<sub>2</sub>-uptake capacities and exceptionally large CO<sub>2</sub>/N<sub>2</sub> adsorption selectivities under ambient conditions.


PPN-6 (also known as PAF-1<sup>4a</sup>) was synthesized by an optimized Yamamoto homocoupling reaction<sup>6</sup> using tetrakis(4bromophenyl)methane. The default diamondoid framework topology imposed by the tetrahedral monomers provides widely open and interconnected pores that efficiently prevent the formation of "dead space";<sup>4b</sup> more importantly, the extremely robust allcarbon scaffold of the network makes it ideal for attachment of polar functionalities on biphenyl species under harsh reaction conditions. By reaction with chlorosulfonic acid, PPN-6 was modified to give PPN-6-SO<sub>3</sub>H, which was further neutralized to produce PPN-6-SO<sub>3</sub>Li (Scheme 1).

Nitrogen gas adsorption/desorption isotherms of the three networks were collected at 77 K [Figure S1a in the Supporting Information (SI)]. Notably, the large desorption hysteresis in PPN-6 disappeared and almost ideal type-I isotherms were obtained for sulfonate-grafted PPN-6. The Brunauer–Emmett–Teller (BET) surface areas obtained from the experimental data were 4023, 1254, and 1186 m<sup>2</sup> g<sup>-1</sup> for PPN-6, PPN-6-SO<sub>3</sub>H, and PPN-6-SO<sub>3</sub>Li, respectively (Figures S2–S4). As expected, the surface area decreased upon functionalization. The pore size distributions of the three networks were derived using the entire range of the N<sub>2</sub> adsorption isotherms measured at 77 K. Along with the decrease in surface area, the pore size became progressively smaller with aromatic sulfonation and ensuing lithiation (Figure S1b).

Received:September 17, 2011Published:October 18, 2011

Scheme 1. Synthesis and Grafting of PPN-6






**Figure 1.** Gravimetric CO<sub>2</sub> and N<sub>2</sub> adsorption ( $\bigcirc$ )/desorption ( $\bigcirc$ ) isotherms at 295 K (see the SI for magnified N<sub>2</sub> isotherm curves).

Recent studies have revealed that one of the desirable features for enhancing the  $CO_2$ -uptake capacity at ambient temperature is a suitable pore size commensurate with the kinetic diameter of a  $CO_2$  molecule.<sup>7</sup> The relatively small pore sizes of both sulfonategrafted PPN-6 networks fall into the 5.0–10.0 Å range, which is believed to be suitable for  $CO_2$  uptake and thus for  $CO_2$  separation from other gases with relatively larger kinetic diameters, such as  $N_2$  and  $CH_4$ .

Strong interactions between the network and CO<sub>2</sub> are another desirable feature for enhancing the CO<sub>2</sub>-uptake capacity. Functionalization of all-carbon-scaffold networks can be expected to create electric fields on the surface that impart to the networks a strong affinity toward CO<sub>2</sub> through its high quadrupole moment. Indeed, the sulfonate-grafted PPN-6 materials displayed significantly enhanced CO<sub>2</sub>-uptake capacities. As shown in Figure 1, nongrafted PPN-6 has a gravimetric CO<sub>2</sub> uptake of 5.1 wt % at 295 K and 1 bar, whereas sulfonate-grafted PPN-6 showed remarkable increases in gravimetric CO2 uptake, with values of 13.1 and 13.5 wt % (equivalent to 3.6 and 3.7 mmol  $g^{-1}$ ) for PPN-6-SO<sub>3</sub>H and PPN-6-SO<sub>3</sub>Li, respectively. To the best of our knowledge, the values are the highest among all microporous organic polymers reported to date.<sup>8</sup> The surge in volumetric uptake with sulfonate grafting is even more significant, from 8.1 g  $L^{-1}$  for PPN-6 to 52.5 g  $L^{-1}$  for PPN-6-SO<sub>3</sub>H and 79.9 g  $L^{-1}$ for PPN-6-SO<sub>3</sub>Li (Figure S5; the tap densities of the three networks used to calculate the volumetric capacities were measured to be 0.15, 0.35, and 0.51 g cm<sup>-3</sup>, respectively). Relative to PPN-6-SO<sub>3</sub>H, the initial CO<sub>2</sub> uptake for PPN-6-SO<sub>3</sub>Li is more pronounced; the  $Li^+$  cation in  $-SO_3Li$  has up to three open coordination sites after full activation, which results in stronger interactions with CO2 molecules.9



**Figure 2.** (a)  $N_2$  adsorption ( $\bigcirc$ )/desorption ( $\bigcirc$ ) isotherms of PPN-6-SO<sub>3</sub>Li at 77 K. (b) Gravimetric CO<sub>2</sub> adsorption curves for PPN-6-SO<sub>3</sub>Li at 273 K. Run 2 employed material regenerated after run 1 by boiling in water for 6 h.





Figure 3. IAST-predicted adsorption selectivities for PPN-6 (red), PPN-6-SO<sub>3</sub>H (green), PPN-6-SO<sub>3</sub>Li (blue), and NaX zeolite (black).

These two sulfonate-grafted PPNs showed no obvious loss of surface area or decrease in  $CO_2$ -uptake capacity even after being boiled in water for 6 h (Figure 2 and Figure S8). Since they were synthesized in highly corrosive acid (ClSO<sub>3</sub>H) and/or base (LiOH) solution, we can be confident of their ultrahigh physicochemical stability.

Aside from high CO<sub>2</sub>-uptake capacity and physicochemical stability, high selectivity for CO2 over N2 under ambient conditions is another prerequisite for industrial CO<sub>2</sub> capture applications. The ideal adsorption solution theory (IAST) of Myers and Prausnitz<sup>10</sup> has been reported to predict binary gas mixture adsorption in many porous materials accurately.<sup>11</sup> To judge the merit of the sulfonate groups for  $CO_2/N_2$  separation, the adsorption selectivities [defined as  $S_{ads} = (q_1/q_2)/(p_1/p_2)$ , where  $q_i$  is the amount of *i* adsorbed and  $p_i$  is the partial pressure of *i* in the mixture] of the three networks for CO2 over N2 in flue-gas streams (typically 15% CO2 and 85% N2) were estimated from the experimental single-component isotherms. Sulfonate-grafted PPN-6 exhibited exceptionally high adsorption selectivity for  $CO_2$  over  $N_2$  at 295 K and 1 bar ( $S_{ads} = 150$  for PPN-6-SO<sub>3</sub>H and 414 for PPN-6-SO<sub>3</sub>Li). As shown in Figure 3, the selectivities of sulfonate-grafted PPN-6 are comparable to that of NaX zeolite, which was calculated with the same parameters using the experimental isotherm data of Belmabkhout et al.<sup>12</sup> and Cavenati et al.<sup>13</sup>. Thus, these materials hold considerable promise for postcombustion carbon capture applications. To understand the hierarchy of adsorption selectivity, we note that the calculated pore volumes for PPN-6, PPN-6-SO<sub>3</sub>H, and PPN-6-SO<sub>3</sub>Li are



**Figure 4.** Isosteric heats of adsorption, as calculated from the adsorption curves at three different temperatures: PPN-6 (red); PPN-6-SO<sub>3</sub>H (green); PPN-6-SO<sub>3</sub>Li (blue).

2.44, 0.58, and 0.52 cm<sup>3</sup> g<sup>-1</sup> respectively. The largest adsorption selectivity in favor of CO<sub>2</sub> is obtained with PPN-6-SO<sub>3</sub>Li, which has the smallest pore volume.

It is worth noting that high CO<sub>2</sub>-uptake capacity at 1 bar does not necessarily lead to a large selectivity for CO<sub>2</sub> over other components of a gas mixture, particularly for low-pressure postcombustion applications where the flue gas usually contains ~15% CO<sub>2</sub>. Thus, a large uptake capacity for CO<sub>2</sub> at 0.15 bar (the partial pressure of CO<sub>2</sub> in flue gas) is more relevant to realistic postcombustion applications. The mass of CO<sub>2</sub> taken up at 0.15 bar divided by the mass of N<sub>2</sub> taken up at 0.75 bar is often used to evaluate CO<sub>2</sub>/N<sub>2</sub> selectivity. The calculated selectivity jumps from 3.0 for PPN-6 to 15 for PPN-6-SO<sub>3</sub>H to 17 for PPN-6-SO<sub>3</sub>Li (Table S2); these values compare well to those other porous materials with high performance, such as metal-loaded MOF-253 (selectivity = 12).<sup>14</sup>

At 295 K and 0.15 bar, the  $CO_2$ -uptake capacity of PPN-6-SO<sub>3</sub>Li is 5.4 wt %. This value is close to the working capacity of 30% MEA solution, which is frequently reported as 5.5 wt %.<sup>15</sup> Notably, the  $CO_2$  sorption isotherms of sulfonate-grafted PPNs are virtually reversible, which indicates a lower generation cost in comparison with MEA solution.

To provide a better understanding of the adsorption properties, the isosteric heats of adsorption were calculated from the CO<sub>2</sub> adsorption isotherms at three different temperatures (Figure 4 and Figures S11-S13). As expected, at zero-loading, PPN-6-SO<sub>3</sub>H and PPN-6-SO<sub>3</sub>Li showed heats of adsorption reaching 30.4 and 35.7 kJ mol<sup>-1</sup>, respectively, which are substantially higher than that of nongrafted PPN-6  $(17 \text{ kJ mol}^{-1})$ . Another acid-functionalized porous polymer (CMP-1-COOH) with similar heat of adsorption  $(32.6 \text{ kJ mol}^{-1})$  has been reported recently.<sup>16</sup> In both cases, the heats of adsorption are much higher than those of the nonpolar, unfunctionalized analogues. The increase for PPN-6-SO<sub>3</sub>H is larger than that for CMP-1-COOH, possibly because of the relatively smaller pore size of CMP-1 than PPN-6. Small pore size has been reported to increase the heat of adsorption.<sup>17</sup> The salt PPN-6-SO<sub>3</sub>Li has an isosteric heat of adsorption that is even higher. The trend is consistent with computational studies suggesting that polar functionalities are effective in increasing the heat of adsorption for CO<sub>2</sub>.<sup>5c,9,18</sup> The discrepancy between PPN-6-SO<sub>3</sub>H and PPN-6-SO<sub>3</sub>Li can be largely attributed to stronger electrostatic interactions between  $CO_2$  and the Li<sup>+</sup> cations.

The general understanding is that the CO<sub>2</sub>-uptake capacity is dictated by many factors, such as surface area, pore functionality, pore size, etc., with each factor carrying different weights at various pressures and temperatures. At very low pressures, the interactions between CO<sub>2</sub> and the pore surface play the dominant role for CO<sub>2</sub> uptake. This appears to be the case for both sulfonate-grafted PPNs, as is most evident in the high heats of adsorption. However, as the pressure is increased to 1 bar, the effect of functionality gradually weakens, and the influence of surface area progressively weighs in, consistent with the decrease of the heat of adsorption.

The foregoing results demonstrate that aromatic sulfonation and ensuing lithiation result in significant enhancements of the  $CO_2$ -uptake capacity and  $CO_2/N_2$  adsorption selectivity under ambient conditions. Given the outstanding physicochemical stability, these materials might find practical applications in postcombustion  $CO_2$  capture. To improve the  $CO_2$ -uptake capacity and  $CO_2/N_2$  selectivity further with this strategy, using porous materials with even higher surface areas as starting materials<sup>4a,f</sup> should have great potential. In addition, uniformly large pores would be ideal for shuttling the reactants and improving the diffusion rates. Moreover, much stronger  $CO_2$ -philic moieties, such as alkylamine groups, would be more effective in increasing the heat of adsorption. <sup>15a,19</sup> Work on further expansion of this series of materials along these lines is currently underway in our lab.

### ASSOCIATED CONTENT

**Supporting Information.** Detailed experimental procedures, elemental analysis results, FT-IR and solid-state NMR spectra, SEM images, additional gas sorption isotherms, and details of the IAST calculations. This material is available free of charge via the Internet at http://pubs.acs.org.

## AUTHOR INFORMATION

## Corresponding Author zhou@mail.chem.tamu.edu

#### ACKNOWLEDGMENT

This work was supported by the U.S. Department of Energy (DE-SC0001015, DE-FC36-07GO17033, and DE-AR0000073), the National Science Foundation (CBET-0930079), and the Welch Foundation (A-1725). We acknowledge Dr. Vladimir Bakhmoutov for his help with solid-state NMR spectroscopy and Dr. Michael Pendleton for his help with the SEM images.

#### REFERENCES

(a) Carbon Dioxide Chemistry: Environmental Issues; Pradier, J. P. C.-M., Ed.; Royal Society of Chemistry: Cambridge, U.K., 1994. (b) MacDowell, N.; Florin, N.; Buchard, A.; Hallett, J.; Galindo, A.; Jackson, G.; Adjiman, C. S.; Williams, C. K.; Shah, N.; Fennell, P. Energy Environ. Sci. 2010, 3, 1645. (c) D'Alessandro, D. M.; McDonald, T. Pure Appl. Chem. 2011, 83, 57. (d) Hao, G. P.; Li, W. C.; Lu, A. H. J. Mater. Chem. 2011, 21, 6447. (e) Wang, Q. A.; Luo, J. Z.; Zhong, Z. Y.; Borgna, A. Energy Environ. Sci. 2011, 4, 42.

(2) (a) Li, J.-R.; Ma, Y.; McCarthy, M. C.; Sculley, J.; Yu, J.; Jeong, H.-K.; Balbuena, P. B.; Zhou, H.-C. *Coord. Chem. Rev.* 2011, 255, 1791.
(b) Mason, J. A.; Sumida, K.; Herm, Z. R.; Krishna, R.; Long, J. R. *Energy Environ. Sci.* 2011, 4, 3030.

(3) (a) D'Alessandro, D. M.; Smit, B.; Long, J. R. Angew. Chem., Int. Ed. 2010, 49, 6058. (b) Keskin, S.; van Heest, T. M.; Sholl, D. S. ChemSusChem 2010, 3, 879.

(4) (a) Ben, T.; Ren, H.; Ma, S. Q.; Cao, D. P.; Lan, J. H.; Jing, X. F.; Wang, W. C.; Xu, J.; Deng, F.; Simmons, J. M.; Qiu, S. L.; Zhu, G. S. Angew. Chem., Int. Ed. 2009, 48, 9457. (b) Lu, W. G.; Yuan, D. Q.; Zhao, D.; Schilling, C. I.; Plietzsch, O.; Muller, T.; Brase, S.; Guenther, J.; Blumel, J.; Krishna, R.; Li, Z.; Zhou, H. C. Chem. Mater. 2010, 22, 5964. (c) Dawson, R.; Laybourn, A.; Khimyak, Y. Z.; Adams, D. J.; Cooper, A. I. Macromolecules 2010, 43, 8524. (d) Holst, J. R.; Stockel, E.; Adams, D. J.; Cooper, A. I. Macromolecules 2010, 43, 8531. (e) Rabbani, M. G.; El-Kaderi, H. M. Chem. Mater. 2011, 23, 1650. (f) Yuan, D.; Lu, W.; Zhao, D.; Zhou, H.-C. Adv. Mater. 2011, 23, 3723. (g) Jiang, J.-X.; Su, F.; Trewin, A.; Wood, C. D.; Campbell, N. L.; Niu, H.; Dickinson, C.; Ganin, A. Y.; Rosseinsky, M. J.; Khimyak, Y. Z.; Cooper, A. I. Angew. Chem., Int. Ed. 2007, 46, 8574. (h) Rose, M.; Bohlmann, W.; Sabo, M.; Kaskel, S. Chem. Commun. 2008, 2462. (i) Germain, J.; Fréchet, J. M. J.; Svec, F. Small 2009, 5, 1098. (j) Germain, J.; Fréchet, J. M. J.; Svec, F. Chem. Commun. 2009, 1526. (k) Yuan, S.; Dorney, B.; White, D.; Kirklin, S.; Zapol, P.; Yu, L.; Liu, D.-J. Chem. Commun. 2010, 46, 4547. (1) Xia, J.; Yuan, S.; Wang, Z.; Kirklin, S.; Dorney, B.; Liu, D.-J.; Yu, L. Macromolecules 2010, 43, 3325.

(5) (a) Dawson, R.; Adams, D. J.; Cooper, A. I. *Chem. Sci.* 2011, *2*, 1173.
(b) Demessence, A.; D'Alessandro, D. M.; Foo, M. L.; Long, J. R. *J. Am. Chem. Soc.* 2009, *131*, 8784. (c) Torrisi, A.; Bell, R. G.; Mellot-Draznieks, C. *Cryst. Growth Des.* 2010, *10*, 2839.

(6) Schmidt, J.; Werner, M.; Thomas, A. Macromolecules 2009, 42, 4426.

(7) Zheng, S. T.; Bu, J. T.; Li, Y. F.; Wu, T.; Zuo, F.; Feng, P. Y.; Bu, X. H. J. Am. Chem. Soc. **2010**, 132, 17062.

(8) (a) Dawson, R.; Stockel, E.; Holst, J. R.; Adams, D. J.; Cooper,
A. I. Energy Environ. Sci. 2011, 4, 4239. (b) Rabbani, M. G.; El-Kaderi,
H. M. Chem. Mater. 2011, 23, 1650.

(9) Xu, Q.; Liu, D. H.; Yang, Q. Y.; Zhong, C. L.; Mi, J. G. J. Mater. Chem. 2010, 20, 706.

(10) Myers, A. L.; Prausnitz, J. M. AlChE J. 1965, 11, 121.

(11) (a) Bae, Y. S.; Farha, O. K.; Hupp, J. T.; Snurr, R. Q. J. Mater. Chem. 2009, 19, 2131. (b) Yazaydin, A. O.; Benin, A. I.; Faheem, S. A.; Jakubczak, P.; Low, J. J.; Willis, R. R.; Snurr, R. Q. Chem. Mater. 2009, 21, 1425. (c) Zheng, B. S.; Bai, J. F.; Duan, J. G.; Wojtas, L.; Zaworotko, M. J. J. Am. Chem. Soc. 2011, 133, 748. (d) Simmons, J. M.; Wu, H.; Zhou, W.; Yildirim, T. Energy Environ. Sci. 2011, 4, 2177. (e) Krishna, R.; van Baten, J. M. Phys. Chem. Chem. Phys. 2011, 13, 10593. (f) Belmabkhout, Y.; Sayari, A. Adsorption 2009, 15, 318. (g) Goj, A.; Sholl, D. S.; Akten, E. D.; Kohen, D. J. Phys. Chem. B 2002, 106, 8367.

(12) Belmabkhout, Y.; Pirngruber, G.; Jolimaitre, E.; Methivier, A. *Adsorption* **2007**, *13*, 341.

(13) Cavenati, S.; Grande, C. A.; Rodrigues, A. E. J. Chem. Eng. Data 2004, 49, 1095.

(14) Bloch, E. D.; Britt, D.; Lee, C.; Doonan, C. J.; Uribe-Romo, F. J.;
 Furukawa, H.; Long, J. R.; Yaghi, O. M. J. Am. Chem. Soc. 2010, 132, 14382.
 (15) (a) McDonald, T. M.; D'Alessandro, D. M.; Krishna, R.; Long,

J. R. Chem. Sci. 2011, 2, 2022. (b) Peeters, A. N. M.; Faaij, A. P. C.; Turkenburg, W. C. Int. J. Greenhouse Gas Control 2007, 1, 396.

(16) Dawson, R.; Adams, D. J.; Cooper, A. I. Chem. Sci. 2011, 2, 1173.

(17) An, J.; Rosi, N. L. J. Am. Chem. Soc. 2010, 132, 5578.

(18) (a) Babarao, R.; Dai, S.; Jiang, D. E. *Langmuir* 2011, 27, 3451.
(b) Liu, B.; Smit, B. *Langmuir* 2009, 25, 5918. (c) Wu, D.; Xu, Q.; Liu, D. H.; Zhong, C. L. J. Phys. Chem. C 2010, 114, 16611.

(19) (a) Arstad, B.; Fjellvag, H.; Kongshaug, K. O.; Swang, O.; Blom, R. *Adsorption* **2008**, *14*, 755. (b) Jin, Y. H.; Voss, B. A.; Jin, A.; Long, H.; Noble, R. D.; Zhang, W. J. Am. Chem. Soc. **2011**, *133*, 6650.